

Robotic Arm

Payload	6kg	
Radius	914mm	
Accuracy	±0.03mm	
Axis	6	
Joints rotation	J1-J6	±360°
	J1-J2	150°/s
	J3	180°/s
Joints speed	J4-J6	230°/s
Typical TCP Speed	1.5 m/s	
IP rating	IP65 (optional IP68)	
Temperature range	-10~50°C	
Relative humidity	<90% (non-condensing)	
Noise reduction	<70db	
Typical power usage	250w	
Mounting	Any angle	
Tool I/O connector	M8, 8pin	
Tool I/O ports	4 config. DI / DO; 1 AI, 1 AO	
Tool I/O power supply	0 / 12V / 24V; 3A / 2A / 1A	
Tool I/O communication	RS485, Modbus RTU	
Footprint	Ø 150 mm	
Weight	20 kg	
Material	Aluminum, steel, plastic, rubber	
Cable length	5.5m*	
Certifications	ISO 13849, ISO 10218, ISO/TS 15066, ISO 14644 cleanroom class 5, RoHS; SEMI-S2; UL, CE, KCs	
Programming	Python-script, graphical proprietary user interface, free-drag/offline programming	

* Optional cable lengths of 1.5m, 3m and 10m and additional extensions up to 10m are available.



Ideal for applications that require a small-sized cobot with sufficient reach and payload, the CS66 cobot is the must-have choice to smoothly automate your light-mid weight pick and place, assembly, dispensing tasks and more.

Standard controller

Type	AC
I/O ports	24 DI, 24 DO (8 safety config. DI/DO); 2 AI, 2 AO; 4 High-Speed DI
I/O power supply	24V/3A (internal), 6A (external)
Communication	RS485, Ethernet TCP/IP, Modbus TCP/RTU, Ethernet/IP slave, Profinet slave
Size	505mm x 257mm 462mm
IP Rating	IP44
Weight	14kg
Power source	100~240 VAC, 50~60 Hz
Temperature range	0~50°C
Relative humidity	5%~95% (non-condensing)
Material	Aluminum, Steel



The standard controller integrates a holder to optionally attach the TP

OEM controller


Type	DC / AC
I/O ports	24 DI, 24 DO (8 safety config. DI/DO); 2 AI, 2 AO; 4 High-Speed DI
I/O power supply	24V/3A (internal), 6A (external)
Communication	RS485, Ethernet TCP/IP, Modbus TCP/RTU, Ethernet/IP slave, Profinet slave
Size	495mm x 200mm x 227mm
IP Rating	IP40
Weight	5kg
Power source	19~72VDC / 100~240VAC, 50~60Hz
Temperature range	0~50°C
Relative humidity	5%~95% (non-condensing)
Material	Aluminum, Steel



The optional OEM controller is suitable for integrators, OEM partners and users who want to create their own custom design.

Teach Pendant

	ERP400	ERP400S
Size	301mm x 232mm x 54mm	301mm x 232mm x 105mm
Screen size	12.1"	
Resolution	1280 x 800 pixels	
IP rating	IP54	
Weight	1.7 kg	1.6 kg
Cable length	5.5 m	
Temperature range	0~50°C	
Relative humidity	5%~95% (non-condensing)	
Material	Aluminum, plastic, rubber	
Input method	Capacitive full touch-screen	Capacitive full touch-screen, 3-mode enable key, jogging-keys, function keys



The CS teach pendant contains Elite Robots proprietary software. The optional ERP400S version integrates jogging and function keys and a 3-mode enable key for enhanced safety.

