

Handy 2000 Series Top-Mounted Cable

Electric Handheld Nutrunner



New lineup with cable connector on top.

Conventional Lineup

Depending on tool orientation during tightening, the cable may interfere with the operation.



New Lineup Top-Mounted Cable

Top-Mounted Cable makes the operation easier.



Select the model that is best for each tightening position.

Tool List

Type	Model	Torque Range		Max. Speed(rpm)		Drive Shaft		Weight		Length		Pulse Drive
		(N·m)	(ft·lb)	200V AC Input	100V AC Input	(mm)	(in)	(kg)	(lb)	(mm)	(in)	
Direct Tools	EH2-R1016-P-T	3.2-16	2.4-11.8	1871	1247	9.5sq	3/8	1.5	3.31	246	9.7	✓
	EH2-R1016-P(PP)-T	3.2-16	2.4-11.8	1871	1247	9.5sq	3/8	1.5	3.31	246	9.7	✓
	EH2-R1016-P(BP)-T	3.2-16	2.4-11.8	1871	1247	9.5sq	3/8	1.5	3.31	246	9.7	✓
	EH2-R1016-PH-T	3.2-16	2.4-11.8	1871	1247	9.5sq	3/8	1.5	3.31	246	9.7	✓
	EH2-R1016-PH(PP)-T	3.2-16	2.4-11.8	1871	1247	9.5sq	3/8	1.5	3.31	246	9.7	✓
	EH2-R1016-PH(BP)-T	3.2-16	2.4-11.8	1871	1247	9.5sq	3/8	1.5	3.31	246	9.7	✓
	EH2-R1020-P-T	4-20	3.0-14.8	1580	1053	9.5sq	3/8	1.5	3.31	246	9.7	✓
	EH2-R1020-P(PP)-T	4-20	3.0-14.8	1580	1053	9.5sq	3/8	1.5	3.31	246	9.7	✓
	EH2-R1020-P(BP)-T	4-20	3.0-14.8	1580	1053	9.5sq	3/8	1.5	3.31	246	9.7	✓
	EH2-R1020-PH-T	4-20	3.0-14.8	1580	1053	9.5sq	3/8	1.5	3.31	246	9.7	✓
	EH2-R1020-PH(PP)-T	4-20	3.0-14.8	1580	1053	9.5sq	3/8	1.5	3.31	246	9.7	✓
	EH2-R1020-PH(BP)-T	4-20	3.0-14.8	1580	1053	9.5sq	3/8	1.5	3.31	246	9.7	✓
	EH2-R2085-PH-T	17-85	12.5-62.7	605	403	12.7sq	1/2	2.8	6.17	361	14.2	
	EH2-R2120-PH-T	24-120	17.7-88.5	438	292	12.7sq	1/2	2.9	6.39	361	14.2	
Pulse Tools (ESTIC PULSE HS)	EH2-H0015-P-T	3-15	2.2-11.1	3075	2000	9.5sq	3/8	1.3	2.87	229.3	9.0	✓
	EH2-H0015-P(PP)-T	3-15	2.2-11.1	3075	2000	9.5sq	3/8	1.3	2.87	229.3	9.0	✓
	EH2-H0015-P(BP)-T	3-15	2.2-11.1	3075	2000	9.5sq	3/8	1.3	2.87	229.3	9.0	✓
	EH2-H1030-P-T	6-30	4.4-22.1	3075	2000	9.5sq	3/8	1.5	3.31	249	9.8	✓
	EH2-H1030-P(PP)-T	6-30	4.4-22.1	3075	2000	9.5sq	3/8	1.5	3.31	249	9.8	✓
	EH2-H1030-P(BP)-T	6-30	4.4-22.1	3075	2000	9.5sq	3/8	1.5	3.31	249	9.8	✓
	EH2-S1050-P-T	10-50	7.4-36.9	2121	1400	12.7sq	1/2	1.8	3.97	278	10.9	✓
	EH2-S1050-P(PP)-T	10-50	7.4-36.9	2121	1400	12.7sq	1/2	1.8	3.97	278	10.9	✓
Pulse Tools (ESTIC PULSE T)	EH2-T0050-P-T	10-50	7.4-36.9	2121	1400	12.7sq	1/2	1.6	3.53	248.3	9.8	✓
	EH2-T0050-P(PP)-T	10-50	7.4-36.9	2121	1400	12.7sq	1/2	1.6	3.53	248.3	9.8	✓
	EH2-T0050-P(BP)-T	10-50	7.4-36.9	2121	1400	12.7sq	1/2	1.6	3.53	248.3	9.8	✓

How to Read the Model Numbers

1 2 3 4 5 6 7
EH2 - R 1 020 - P (PP) - T

- Series**
- Fastening Mode**
 R : Direct Fastening
 H : High Speed Pulse Fastening (ESTIC PULSE HS)
 S : High Speed Pulse Fastening (ESTIC PULSE HS)
 T : Pulse Fastening for Hard Joints (ESTIC PULSE T)
- Motor Output**
 0 : 50W
 1 : 100W
 2 : 200W-1
- Max. Rated Torque**
 000 : 3Digits N·m
- Tool Type**
 P : Pistol
 PH : Pistol, with Splines or Flange
- Drive Shaft**
 Blank : Through Hole
 (PP) : Pin Plunger
 (BP) : Ball Plunger
- Cable Connector Specification**
 T : Top-Mounted Cable

Supported controllers

Handy 2000 Lite plus / Touch

(Controller model Lite plus : EH2-HT45-000*** / Touch : EH2-HT50-000***)

● For controller specifications, please refer to the Handy 2000 Series GENERAL CATALOG.

● CAD data can be downloaded from our website.

<https://www.estic-global.com/member>



Handy 2000 Series GENERAL CATALOG

ESTIC CORPORATION

1-2-16 Togodori, Moriguchi-city,
Osaka, 570-0041 Japan



JP : www.estic.co.jp
 EN : www.estic.co.jp/en/
 CN : www.estic.co.jp/cn/



www.youtube.com/user/EsticCorporation



www.linkedin.com/company/estic-corporation



JQA-2805

