

TEXTURED		STUDED		CHEQUER		EXCEL		SLATE	
<b>SIZE</b> 503 x 503mm		<b>SIZE</b> 503 x 503mm		<b>SIZE</b> 503 x 503mm		<b>SIZE</b> 503 x 503mm		<b>SIZE</b> 456 x 456mm	
<b>THICKNESS</b> EN438 - 4, 5, 7, & 9mm		<b>THICKNESS</b> EN438 - 5 & 7mm		<b>THICKNESS</b> EN438 - 4, 5 & 7mm		<b>THICKNESS</b> EN438 - 5mm		<b>THICKNESS</b> EN438 - 6mm	
<b>WEIGHT</b> 4mm - 6.4kg/m <sup>2</sup> 5mm - 7kg/m <sup>2</sup> 7mm - 9.21kg/m <sup>2</sup> 9mm - 12.8kg/m <sup>2</sup>		<b>WEIGHT</b> 5mm - 7kg/m <sup>2</sup> 7mm - 9.21kg/m <sup>2</sup>		<b>WEIGHT</b> 4mm - 6.4kg/m <sup>2</sup>		<b>WEIGHT</b> 5mm - 7kg/m <sup>2</sup> 7mm - 9.21kg/m <sup>2</sup>		<b>WEIGHT</b> 6mm - 8kg/m <sup>2</sup>	
<b>Tiles Per Box</b>	<b>M<sup>2</sup> Per Box</b>	<b>Tiles Per Box</b>	<b>M<sup>2</sup> Per Box</b>	<b>Tiles Per Box</b>	<b>M<sup>2</sup> Per Box</b>	<b>Tiles Per Box</b>	<b>M<sup>2</sup> Per Box</b>	<b>Tiles Per Box</b>	<b>M<sup>2</sup> Per Box</b>
4mm Qty 12	3m <sup>2</sup>	5mm Qty 10	2.5m <sup>2</sup>	5mm Qty 10	2.5m <sup>2</sup>	5mm Qty 10	2.5m <sup>2</sup>	6mm Qty 6	1.25m <sup>2</sup>
5mm Qty 10	2.5m <sup>2</sup>	7mm Qty 8	2m <sup>2</sup>	7mm Qty 8	2m <sup>2</sup>	7mm Qty 8	2m <sup>2</sup>		
7mm Qty 8	2m <sup>2</sup>								
9mm Qty 6	1.5m <sup>2</sup>								

## CLASSIFICATION

Norm / Product specification	-	EN ISO 10581
European Classification	EN ISO 10874	34/43
Fire Class	EN 13 501-1	Bfl-s1
Static Electrical Propensity	EN 1815	2 kV
Slip Resistance	EN 16165 app. B DIN 51130	R10

## PERFORMANCE

Wear Resistance	EN 660.2	<2.0mm <sup>3</sup>
Wear Group	-	T Group
Dimensional Stability	EN ISO 23999	≤0.25%
Dimensional Stability(average measured value)	-	≤0.10%
Residual indentation	EN ISO 24343-1	0.1mm
Castor Chair Test (type W)	ISO 4918	Ok
Colour Fastness	EN 20 105 - B02	Ok
Chemical Products Resistance	EN ISO 26987	Ok
Flexibility	ISO 24344 Method A	No Cracking
Shore Hardness	EN ISO 868	>40 H <sub>D</sub>
Type Binder Content	ISO 10581	I Group
Thermal Conductivity	ISO 8302	0.25 W/(m.K)

## ENVIRONMENTAL ACCREDITATIONS

TVOC after 28 days	ISO 16000-6	< 100 µg/m <sup>3</sup>
Certification	-	Floorscore®

## CE MARKING



EN 14041

